

PRODUCT INFORMATION



Lubricants - Engine Oil - Motorcycle Motor Oils

Valvoline™ DuraBlend™ 4T 10W-40

High performance semi synthetic motor oil for four-stroke motorcycle engines.
Formulated to meet the requirements of all leading engine manufacturers.

Performance levels

API SL
JASO MA
JASO MA2

Applications

Four-stroke motorcycle engines where API SL or JASO MA or JASO MA2 fluids are required.

Optimized for lubrication systems where engine, gearbox and clutch are integrated (wet sump).

Suitable for motorcycles running in cold weather conditions.

Features & Benefits

High performance

Durablend 4T engine oil is formulated with high quality base oils and additives to ensure maximum performance output for two wheel vehicles.

Wet clutch compatible

Optimal frictional characteristics for maximum power transfer, smooth shifting and proper protection of the wet clutch. (JASO MA approved).

Wear protection

Strong oil film and enhanced product stability provide long lasting engine protection.

Engine cleanliness

Keeps the engine clean by minimizing deposits.

Easy starts

Recommended for quick starting. Even under very cold conditions or after long periods of engine inactivity.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline Global Operations is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit <https://www.valvolineglobal.com/en-eur/> or <http://pisheets.valvolineglobal.com>

Health & Safety

For more information about environment requirements, product safe handling, storage, and disposal, please refer to the product Safety Data Sheet (SDS) available at <http://sds.valvolineglobal.com>

Typical properties

DuraBlend 4T	
SAE Viscosity Grade	10W-40
Viscosity @ 100°C, mm²/s ASTM D445	14.8
Viscosity @ 40°C, mm²/s ASTM D445	98.0
Viscosity Index ASTM D2270	158
TBN, mg KOH/g ASTM D2896	7.3
Pour Point, °C ASTM D5949	-36
Density @ 15°C, g/cm³ ASTM D1298	0.865
Flash Point, COC, °C ASTM D92	228

*The data provided is for reference only and can be applied only for the specific production location.

This information only applies to products manufactured in the following location(s): Europe

Effective date: 3/30/2026